

## LMP7/35D Mini Concrete Pump

**MUCH BETTER PERFORMANCE SAFE RELIABLE**

### Brief-introduction:

LMP7/35D pump is one multi-purpose industrial pump developed by absorbing advanced technology from abroad, driven by diesel engine, max. output could be arrive to 7m<sup>3</sup>/h, working pressure is 35Bar, so widely used for concrete pumping or grouting and shotcreting work.



Solid tyres, feel free to move;  
Independent electric control cabinet;  
Convenient for operation and longevity of service.



Changchai L32 diesel engine  
Electric-start, with  
peed-regulating handle,  
quality guarantee, easy to  
operate.

Output 3-7m<sup>3</sup>/h, stepless  
adjustable, more widely  
application for grouting and  
spraying work.



Specially design spraying nozzle,  
spraying flow is even, continuous and  
steady.

### Technical data sheet:

Rated Output: 3-7m<sup>3</sup>/h

Pump Work Pressure: 35Bar

Acceptable Max. Aggregate Size: 20mm

Cylinder Diameter: Ø120mm

Cylinder Stroke: 360mm

Pump Valve: S Valve

Max. Horizontal Conveying Distance: 90m

Max. Vertical Conveying Distance: 30m

Concrete Slump: 15-25cm

Conveying Hose Inner Diameter: 80/100mm

Diesel: 23kw/2200rpm single cylinder, water cooling

Dimension(L x W x H): 2200\*1250\*1600mm

Net Weight: 1190kg

### Application:


- Concrete wall construction;
- Masonry block filling;
- Concrete wall grouting;
- Concrete sidewalk;
- Patio slab pumping;
- Low-volume shotcrete;
- Tunneling construction;
- Mining support (sprayed concrete walls and ceilings);
- Swimming pool (sprayed concrete shells);
- Excavation-protection.



If for shotcreting,  
need work with  
dosing pump and  
air compressor.



Cemented Carbide  
Wear Plate/Ring  
(working life more than  
10000m<sup>2</sup>).



Polyether material  
piston, more  
wear-resisting.