

Zhengzhou Lead Equipment Co., Ltd.

地址 ADD: 郑州市中原区西流湖街道办事处铁炉村西四环东 邮编 P.C.:450042

Xisihuan Ring-Road East, Tielu, Xiliu lake sub-district, Zhongyuan District, Zhengzhou, Henan

电话 TEL: +86-371-63902781 传真 FAX:+86-371-63526676

LP30 Precast Foam Cement Wall Panel Machine

Brief Instruction:

LP30 Precast Foam Cement Wall Panel Machine is a lightweight concrete derived from Portland cement and common Portland cement as inorganic cementing material, fly ash as admixture, sand as aggregate, mixed with organic foaming agent. Non-load-bearing walls constructed by cast-in-situ foamed concrete has changed the traditional way of building walls with precast concrete segments. The excellent integrity and easy operation means low labour intensity and low building cost. Besides, good strength characteristics with reduced weight, excellent sound and thermal insulation, and water proof, etc., all these performances make it an ideal substitute of present traditional walls.

Features:

- 1. Adopting wear resistant metal, sturdy and durable.
- 2. Adopting the famous brand good quality components, reliable quality.
- 3. Adopting hydraulic two cylinders single conveying way to send the foam concrete to the construction plant on-site, stable flow, small fluctuation.
- 4. Equipped with travelling wheels foothold, easy to move and fix.
- 5. Equip the remote control handle with the electric cabinet, convenient operation.













Zhengzhou Lead Equipment Co., Ltd.

地址 ADD: 郑州市中原区西流湖街道办事处铁炉村西四环东 邮编 P.C.:450042

Xisihuan Ring-Road East, Tielu, Xiliu lake sub-district, Zhongyuan District, Zhengzhou, Henan

电话 TEL: +86-371-63902781 传真 FAX:+86-371-63526676

Technical data:

Model	LP30
Max. Output	30 m3/h
Max. Conveying Pressure	4 MPa
Max. Horizontal Transporting Range	500 m
Max. Vertical Transporting Height	180 m
Max. Particle Size of Aggregates	8 mm
Cylinder Bore	80 mm
Delivery Cylinder Bore	140 mm
Max. Pressure of Hydraulic System	24 MPa
Oil Pressure Box Volume	320 L
Motor Power	22.18 kw
Voltage	3 Phase, 380 V, 50Hz
Total Weight	2000 kg
Overall Dimension	4200x1420 x1700mm



Zhengzhou Lead Equipment Co., Ltd.

地址 ADD: 郑州市中原区西流湖街道办事处铁炉村西四环东 邮编 P.C.:450042

Xisihuan Ring-Road East, Tielu, Xiliu lake sub-district,

Zhongyuan District, Zhengzhou, Henan

电话 TEL: +86-371-63902781 传真 FAX:+86-371-63526676

foaming agent

The foaming agent is a high-tech product, it has the characteristics as high expansion ratio, balanced density, foaming stability, and a long continuance, etc. Thus it is an environmental protective mighty foaming agent, which is nuisance-free and pollution-free.



Working pictures:





Zhengzhou Lead Equipment Co., Ltd. 地址 ADD: 郑州市中原区西流湖街道办事处铁炉村西四环东 邮编 P.C

邮编 P.C.:450042

Xisihuan Ring-Road East, Tielu, Xiliu lake sub-district,

Zhongyuan District, Zhengzhou,Henan

电话 TEL: +86-371-63902781 传真 FAX:+86-371-63526676

Package and delivery:





Attached parts:















Applications:







Zhengzhou Lead Equipment Co., Ltd.

地址 ADD: 郑州市中原区西流湖街道办事处铁炉村西四环东 邮编 P.C.:450042

Xisihuan Ring-Road East, Tielu,Xiliu lake sub-district, Zhongyuan District, Zhengzhou,Henan

网址(Web):http://www.leadcrete.com E-Mail: sales@leadcrete.com

电话 TEL: +86-371-63902781 传真 FAX:+86-371-63526676

Zhengzhou Lead Equipment Co., Ltd.

Add: Xisihuan Ring-Road East, Tielu, Xiliu lake sub-district,

Zhongyuan District, Zhengzhou, Henan

Web: http://www.leadcrete.com E-Mail: sales@leadcrete.com

TEL: +86-371-63902781 FAX:+86-371-63526676