LGP200/300/100PI-E grout plant manufacturers

Feature:

- 1. It is combination of mixer, agitator and hydraulic grout pump in one base frame.
- 2. Siemens electric motor(WEG electric motor is optional)
- 3. Schneider component for electric control box.
- 4. Yuken reversing valve for hydraulic system of grout pump
- 5. Butterfly valve of mixer and agitator.
- 6. Linked switch between mixer and agitator.
- 7. Oil temperature gauge can automatically control cooler fan working in normal temperature range, if temperature is too high, the machine will stop work automatically.

Technical data:

Description	Data
Grout Station type	LGP200/300/100PI-E
Mixer Volume	200L
Mixer production(w/c ratio=1)	4m3/h
Circulation capacity	1100L/min
Suitable W/C Ratio	0.5 to 1
Mixer electric motor power	7.5kw, 1450rpm
Agitator Volume	300L
Agitator Speed	36rpm
Agitator electric motor power	1.5kw, 1450rpm
Water tank	60L
Grout Pump Type	LGH90
Grout pump output(Max.)	100L/min
Grout pump work pressure	10MPa
Grout pump electric motor power	11kw, 1450rpm
Grout Station Overall dimension	2400x2300x1620mm
Grout Station Weight	1320kgs

Certificate:

CE AND ISO9001-2008





Version:March.2013 Copyright@Lead Equipment Co., Ltd.



















