

郑州佰利得机器制造有限公司

Zhengzhou Lead Equipment Co., Ltd.

地址 ADD: 郑州市中原区西流湖街道办事处铁炉村西四环东

邮编 P.C.:450042


Xisihuan Ring-Road East, Tielu, Xiliu lake sub-district,

Zhongyuan District, Zhengzhou, Henan

网址(Web):http://www.leadcrete.com E-Mail: sales@leadcrete.com

电话 TEL: +86-371-63902781 传真 FAX:+86-371-63526676

LH100-915B China Foam Concrete Pump for Sale



Description

LH100-915B China Foam Concrete Pump for Sale consists mainly of pump house, rotor, roller, idle roller, squeeze tube and driving unit. The squeeze hose is U-shape in pump house, when rotor drives roller to rotate, hose is deformed. After the roller rotate, the deformed hose recover by its elasticity.

Thus the negative pressure in this hose is generated, sucking slurries, and discharging through outlet under roller's push, finally forms pressure conveying of slurries.

▶ Application

- ♦ LH series industrial hose pump are mainly applied in distant conveying, grouting and dosing of viscous slurries in construction, mining, food, papermaking, ceramic, etc.
- ♦ LEC industrial peristaltic pumps can be used in following field: Construction, pharmacy, textile mill, dye making, water treatment, paper making, mining, ceramic, brewery and beverage, underground engineering, etc. It's perfect to pump corrosive, abrasives, shear



郑州佰利得机器制造有限公司

Zhengzhou Lead Equipment Co., Ltd.

地址 ADD: 郑州市中原区西流湖街道办事处铁炉村西四环东

邮编 P.C.:450042

Xisihuan Ring-Road East, Tielu, Xiliu lake sub-district,

Zhongyuan District, Zhengzhou, Henan

电话 TEL: +86-371-63902781 传真 FAX:+86-371-63526676

sensitive fluids, high viscosity fluids, high density fluids, large solids, metering(±1%), high pressure(3Mpa).LH series industrial hose pump are mainly applied in distant conveying, grouting and dosing of viscous slurries in construction, mining, food, papermaking, ceramic, etc.

Features

- ♦ No seals
- ♦ No valves
- ♦ Self -priming
- ♦ Only tube to replace
- ◆ Dry –running without damage
- ♦ Reversible
- ♦ No contact between product and mechanical parts
- ♦ Able to pump products with solid parts inside
- ♦ Easy maintenance, low-cost, short down time

► Technical Data:

Туре	LH100-915B
Max. output	40m3/h
Rotation	45 RPM
Squeeze hose ID	102mm
Working pressure	7.5 bar
Voltage	3 phase, 380V, 50HZ
Power	18.5 KW

Zhengzhou Lead Equipment Co., Ltd.

Add: Xisihuan Ring-Road East, Tielu,Xiliu lake sub-district, Zhongyuan District, Zhengzhou,Henan

Web: http://www.leadcrete.com E-Mail: sales@leadcrete.com

TEL: +86-371-63902781 FAX:+86-371-63526676