

LZ-3AR Refractory Gunite Machine



地址 ADD: 郑州市中原区西流湖街道办事处铁炉村西四环东 邮编 P.C.:450042
Xisihuan Ring-Road East, Tielu, Xiliu lake sub-district,
Zhongyuan District, Zhengzhou, Henan

网址 (Web): www.leadcrete.com E-Mail: sales@leadcrete.com

电话 TEL.: +86-371-63902781 传真 FAX: +86-371-63526676

Description

LZ-3AR Refractory Guniting Machine is specifically designed for refractory dry-mix shotcrete gunning applications with air motor drive. With this LZ-3AR, you can get low dust, low bound and high performance spraying flow in nozzle.

Application

It can be used for refractory spraying applications, as well as for concrete shotcrete application.

LZ-3AR Refractory Guniting Machine is widely used for spraying refractory materials, castable in steel plant. Equipped with ABB frequency converter could achieve variable output from 1m³/h to 3m³/h.

Features

1. Variable Output. 5 cylinders piston air motor drive
2. Bag cutter and flat hopper with vibrator
3. Collect dust bag
4. Clean dust gun
5. Heavy-duty solid wheels
6. Coupling and clamp
7. Light weight nozzle
8. Blast rubber hose

地址 ADD: 郑州市中原区西流湖街道办事处铁炉村西四环东

邮编 P.C.:450042

Xisihuan Ring-Road East, Tielu, Xiliu lake sub-district,
Zhongyuan District, Zhengzhou, Henan网址 (Web) :www.leadcrete.com E-Mail: sales@leadcrete.com

电话 TEL.:+86-371-63902781 传真 FAX:+86-371-63526676

Technical Data

Rated Output	1-3m ³ /h (2-6 ton/h)
Max. Horizontal Conveying Distance	200m
Max. Aggregate Size	Φ10 mm
Conveying Hose Inner Diameter	38mm
Operating air Pressure	0.2-0.4MPa(29-58PSI)
Air Consumption	10-11m ³ /min
Engine	4kw
Material Charging Height	1.1m
Rotor Speed	13.2r/min
Overall Dimension(LxWxH)	1.13x0.54x1.1m
Weight	430kg